



# Bright Ceiling Coat

## PRODUCT DESCRIPTION

Indigo Bright Ceiling Paint is specially formulated to provide minimal spatter and excellent coverage with High Brightness. It hides minor surface imperfection and dries quickly to give a smooth even finish.



## PERFORMANCE FEATURES & BENEFITS

1. Uniform finish
2. High Brightness
3. Easy to apply
4. No Odour

### FINISH

**MATT**

SEMI GLOSSY

### WASHABILITY

NO

**LOW**

MEDIUM

HIGH

## RECOMMENDED USES

### AREA

Interior Ceiling

### SURFACES

Concrete, Plastered walls and Interior Ceilings

## APPLICATION DETAILS & SURFACE PREPARATION

### MIXING



Shake well before use

### TOOLS



Brush, Roller &amp; Spray

### THINNING



Water

### THINNING RATIO



50-60% by Volume

### SURFACE DRYING TIME



Surface Dry in 30 Min.

### FILLING



Indigo Polymer Putty or Acrylic Wall Putty

### APPLICATION ENVIRONMENT


 Temperature: 10-40 Degree  
 Humidity: Below 70%

### CLEANING



Sand the surface with Emery paper 180 and wipe clean.

### SURFACE PREPARATION



Apply a coat of Indigo Primer, allow drying for 6-8 hours. Smoothen the surface by filling dents with thin coats of Indigo Acrylic Wall Putty. After drying for 6-8 hours, sand the surface with Emery paper 180. Wipe off loose particles. Apply another coat of primer. Allow drying for 4-6 hrs. Sand the surface with Emery paper 380 and wipe clean.

### APPLICATION



Apply 2-3 coats of Indigo Bright Ceiling Coat, obtained by thinning 1 L of emulsion with 500-600 ml of water.

### SAFETY FEATURES



Non- flammable  
 No added Lead, Mercury or Chromium compounds

## TECHNICAL DATA

<b>Coverage</b>	1st Coat: 9 - 11 sqm/L* 2nd Coat: 6 - 7 sqm/L*
<b>Drying Time</b>	4-5Hrs
<b>Sheen level</b>	2.4 at 60 deg
<b>Flash point</b>	NA
<b>Stability of thinned paint</b>	24Hrs
<b>Appearance</b>	Smooth, Liquid, Milky White
<b>Solids</b>	54
<b>Specific gravity</b>	1.39
<b>Recommended DFT</b>	NA
<b>Viscosity @25°C by Stormer Viscometer</b>	2200 CP
<b>Pot life</b>	24 Hrs
<b>Shelf life</b>	24 Months
<b>Contrast ratio</b>	98.79

\*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.

## PRECAUTIONS

1. Wall should be free from moisture
2. If any wall is under seepage, treat it with proper waterproofing
3. Do not apply on any lime washed surfaces
4. In case of fungi or algae use Indigo Bio Clean to clean the surface

## POST APPLICATION INSTRUCTIONS

1. Painted surfaces can be washed after 30 days with mild detergent and cellulose sponge.
2. Do not use harsh, abrasive cleaners.

## AVAILABLE PACK SIZE

Available in:



## SHADE RANGE

White

